

PRODUCT SPECIFICATION

INDUCT

Range: Ventilation Range

Model: Light, Standard, Pro, Ultra, Ultra+, Ultra Max

Description: HVAC Air Purification and Disinfection

Power information:


	Induct Light-Ultra	Induct Ultra+	Induct Ultra Max
Power Adapter:	12VDC, 2.0A		12VDC, 5.0A
Power Inlet:	110-240VAC, 50-60Hz		
Power Consumption:	<15W	<30W	<40W
Operating Temperature:	-20°C - +40°C (68°F - 104°F)		
Humidity:	0-90% RH non-condensing		
Lamp Life:	One Year		

Features:

- Effective odour, smoke and chemical reduction
- Various placement options (SAD, FAD, RAD ducts)
- Fast and simple installation process
- Requires just one annual lamp replacement
- Completely automated and chemical free

Applications:

- Odour Removal
- Smoke Removal
- Bacteria Reduction
- Refreshed Indoor Spaces
- Commercial Buildings
- Offices and Workplaces
- Hotels and Restaurants
- Hospitals and Clinics



Warranty:

One year parts and labour on entire unit. An additional one year warranty is available when the warranty card is submitted.

PRODUCT SPECIFICATION

INDUCT

Range: Ventilation Range

Model: Light, Standard, Pro, Ultra, Ultra+, Ultra Max

Description: HVAC Air Purification and Disinfection

Specifications:

	Induct Light-Ultra	Induct Ultra+	Induct Ultra Max
Length:	200mm	200mm	300mm
Width:	100mm	100mm	100mm
Height:	76mm	76mm	76mm
Weight:	640g	730g	980g
Colour:	Silver	Silver	Silver

Reorder Information:

Light:	10-08010
Standard:	10-08025
Pro:	10-08050
Ultra:	10-08100
Ultra+:	10-11100
Ultra Max:	10-15100

Contents:

1 Induct Unit



2 Photoplasma™ Lamp (8", 11" or 15")



3 Installation Screws and Clips



4 Owners Manual

